

Tools Series

HS-28C

Crimping cap (For Non-insulated closed terminals)
Capacity mm²:6-10
Length mm:270
Weight kg:0.55



HS-6M

Crimping cap (For Non-insulated closed terminals)
Capacity mm²:1-10
Length mm:250
Weight kg:0.35



HS-8

For non-insulated cable link
Capacity mm²:1.25-8
Length mm:270
Weight kg:0.55



HS-13

Crimping cap (For Non-insulated closed terminals)
Capacity mm²:0.5-6
Length mm:270
Weight kg:0.55



HS-14

For non-insulated cable link
Capacity mm²:5.5-14
Length mm:270
Weight kg:0.55



HS-16

For Non-insulated cable links
Capacity mm²:1.25-16
Length mm:270
Weight kg:0.55



HX-4

For non-insulated cable link
Capacity mm²:1-4
Length mm:270
Weight kg:0.55



HX-10

For non-insulated cable link
Capacity mm²:2-10
Length mm:270
Weight kg:0.55



HX-16

For non-insulated cable link
Capacity mm²:6-16
Length mm:270
Weight kg:0.55



HX-26B

For non-insulated cable link
Capacity mm²:6-26
Length mm:354
Weight kg:0.85



HS-22

For non-insulated cable link
Capacity mm²:5.5-25
Length mm:354
Weight kg:0.85



HS-38

For non-insulated cable link
Capacity mm²:6-38
Length mm:356
Weight kg:0.85



HX-120B

For non-insulated cable link
Capacity mm²:10-120
Length mm:620
Weight kg:4



HX-50B

For non-insulated cable link
Capacity mm²:6-50
Length mm:390
Weight kg:1.3



HX-245B

For non-insulated cable link
Capacity mm²:70-240
Length mm:980
Weight kg:5.6



HX-150B

For non-insulated cable link
Capacity mm²:25-150
Length mm:620
Weight kg:4



CT-38

For non-insulated cable links
Capacity mm²:8-38
Length mm:570
Weight kg:2.2



CT-80

For non-insulated cable links
Capacity mm²:8-80
Length mm:635
Weight kg:3.2



CT-150

For non-insulated cable links
Capacity mm²:16-150
Length mm:765
Weight kg:5.2



KH-150

For non-insulated cable links
Capacity mm²:10-120AL/CU
Length mm:610
Weight kg:3.1



KH-230

For non-insulated cable links
Capacity mm²:10-240AL/CU
Length mm:980
Weight kg:4.7

